

JET 570

Technical sheet

Recommended use : Light box

Range :

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values			Units	Standards
	Warp	Weft			
General characteristics					
Thickness	0.49			mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den				
Coating	PVC coating one side			Inkjet	
Finish	lacquer one side				
Weight	570			g/m ²	ISO 3801
Translucency	23			%	XPT 54199
Width	137	162	320	cm	
Roll length	30	30	60	ml	

Fabric resistance

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	DIN 53.363
Adhesion	9		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
	M2			NF P 92 503
Fire resistance	B1			DIN 4102
	NFPA 701			NFPA 701



AnsonFabrics Co.

No.36 Fenghuang Road
Qianjiang Industry Zone

Haining, 314413

82.5730.5258

(customer service)

86.182.5832.6285

INFO@ANSONFABRICS.COM



RESOURCE

